

AMENDMENTS TO THE CLAIMS

The following listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1 (Currently Amended): A process for operation of an active electro-optical filtering device for dazzle protection with an active optical filter element (1), wherein the optical filter element (1) is driven with anti-polar drive pulses, ~~whereby~~ and wherein the optical filter element (1) is short-circuited between two successive drive pulses.

B1
Claim 2 (Previously Presented): The process in accordance with claim 1, wherein short-circuit times (t_{s1} , t_{s2}) are shorter by factors in the order of magnitude of 10^3 to 10^7 than time durations (t_+ , t_-) of the drive pulses.

Claim 3 (Previously Presented): The process in accordance with claim 1, wherein a framework frequency (f) of the drive pulses amounts to between 0.01 and 1 Hz.

Claim 4 (Previously Presented): The process in accordance with claim 1, wherein an operating voltage (U_{LC}) is applied to the optical filter element at which operating voltage (U_{LC}) the scattered light term (Φ_{1R}) of the optical filter element (1) is smaller than or equal to a transmission term of the optical filter element (1).

Claim 5 (Previously Presented): The process in with claim 4, wherein the operating voltage (U_{LC}) lies several times above a Fréedericksz-threshold of the optical filter element (1).

B1
Claim 6 (Currently Amended): An active electro-optical filtering device ~~that is adapted for operation in accordance with the process of claim 1, said filtering device containing~~ comprising: at least one active optical filter element (1) with a liquid crystal, electronic means (2) for driving the at least one active filter element (1), a light sensor (4) operating in conjunction with the electronic means (2) and electric power supply means (5), in particular a solar cell, for the electronic means (2) and the at least one optical filter element (1), ~~and~~ wherein the liquid crystal is implemented in accordance with a technology selected from the group consisting of: TN-technology, STN-technology, dichroic technology, ferro-electric technology and π -Mode-LCD-technology, wherein the optical filter element (1) is driven with anti-polar drive pulses, and wherein the optical filter element (1) is short-circuited between two successive drive pulses.

Claim 7 (Previously Presented): The drive circuit (2) for an active electro-optical filtering device in accordance with claim 6, further comprising a switch (S_1) with which the active optical filter element (1) can be short-circuited.
